

## **IP43 Cabinet**

Outdoor Cabinet with CCTV Equipment



## **Overview**

- > Suitable for outdoor applications (Standard type), suitable for CCTV system.
- > Suitable for Fiber Optic Equipment , Industrial Media Converter and Industrial Ethernet Switches.
- > Body made from Electro Gavanized Sheet Steel with 1.0mm thinkness (Light weight and completed rust proof).
- > One layer design, suitable for outdoor installation better protection (IP43 rating).
- > Electrostatic Powder Coating outdoor paint with international standards ASTM- D3363, ASTM-D3359 and ASTM-D522.
- > One front door lockable (with Master key), Made of EG Steel (Electro galvanized steel).
- > Build-in Push Handle Lock at front door.
- > Water-proof and ventilation by roofer at 2 side panels with dust filter and insects protection.
- > Provided CNC Foam Gasket Technology on door for protection water, humidity, dust & rustproof and roof of cabinet protect or shield waterproof by rubber back.
- > Supporting by double steel bar with thickness of 2.0 mm. at back side for mounting on wall or electrical pole.
- > Can be mounted with one 4" ventilation fan on roof cover with thermostat controller (can set working temperature to the fan), release the accumulated heat inside the cabinet and extend the life of equipment.
- > Provide rubber shield on the roof and door to prevent water and dust.
- > Provide 3 knock out holes with size 3/4" for communication cable and 1" for power cable entry.
- > Provide cable guide inside the cabinet for manages all the cable.
- > Provide removable component plate with thickness 1.5 mm. and provide Din Rail for install the Industral Media Converter or Industrial Switch. And it support fusion splice tray installation.
- > Built-in 2-Socket universal 220VAC plugs and circuit breaker.
- > Size : 430 mm x 680 mm x 250 mm (Width x High x Depth).
- > Provide busbars and ground wire connecting between structure cabinet and front door.
- > Built-in standard electrical socket, circuit breaker and surge protector (Optional).

## **Accessories (Optional)**

- Industrial Power Supply > Input : 220 VAC
- > Output : 48 VDC
- > Output Power : 120 W
- > 89% Efficiency



L2 Industrial Switch > 8 x RJ45 10/100/1000 Mbps

> 8 x POE port (IEEE 802.3af/at)

> 2 x SFP slot



UPS (Battery backup)

- > Charger controller
- > Up to 60 min. backup time
- > Built-in Surge Protection
- > Short circuit & Overload protection

RM 1202, 12/F,TUNG CHUN COMMERCIAL CENTRE, 438-444 SHANGHAI STREET, KOWLOON, HONGKON