

SG-C43-A/B

IP43 CCTV Outdoor Cabinet



Description

A cabinet for outdoor installation Wall mounting. Surveillance equipment (CCTV) installed equipment stay. And fiber optic dustribution, Industrial MediaConvertor.Industrial Ethernet Switches

This model have 2 dimensions option SG-C43-A = H $68 \times W 43 \times D 20 \text{ cm}$ SG-C43-B = H $74 \times W 50 \times D 25 \text{ cm}$

Accessories



Heavy Duty Cooling Fan (Optional: 1x4" or 2x4")



AC Power Outlet (Optional: 4 or 6 Outlet)

Features

- · Made by Electro galvanize steel thickness 1.0 mm. it does not rust and is lightweight including green-yellow ground wire size 2.5mm.
- There are 4 gland audio cables to hold the cable and have a wire interconnected between Cabinet lid and cabinet to prevent short circuit current.
- The color of the cabinet for a special kind of external.Dark gray Through a color system with the painting process Electro-static Powder / Epoxy polyester coating international standard ASTM.
- Front-door key lock Push Handle Lock Twist caps cabinet to increase security even more.
- Both sides Drilling ventilation fins to protect the bugs, dust and water.
- 2 mm. thick steel rear support for the cabinet to seize power pole.
- Roof rack can be mounted blower 4 "has two built-in cabinets can be cooled well. And help extend the useful life of the equipment inside the cabinet.
- Cover container and container roof with a rubber shield around the cabinet to prevent waterfrom entering inside, using CNC Foam Gasket Technology.
- Inside pad (Plate) for lead 1.5 mm. Aladdin could removable for mounting to be installed insidethe cabinet and build Din Rail
 mounting, Industrial Media Converter and Industrial Ethernet Swiches.
- 3 hole perforated base cabinet size 3/4 inch and 1 inch for attaching to the cabinet.
- Inside the cabinet there is a Cable Wire Guide for fixing the cables
- The plate has a Stud nut, can be installed in two layers (stacked) and has a plate to hold the Adapter snap Plate 2 Plate supports fiber optic up to 24 Core.
- Ground connection cable between the cabinet and the lid of the cabinet.
- Can be ground wire, Splice tray, Cable Wire Guide, Cable Management, Surge and Breaker in cabinet
- · Have roof for rain protection.
- Dust and Water protection: IP 43 rating.
- Support 2 x 4" Fan ventelation on top or side of cabinet (Optional).