



# SHOGUN

## SG-714/716

### 14/16 Slot Rack-Mountable Media Converter Chassis



#### Features

- > Standard chassis 19", the rack can be installed in the room, be easy to unified management and maintenance
- > Adopted modular power supply design, easy to maintain, shielding is better
- > Preventing electromagnetic interference on the power supply from the normal operation of the modules
- > 16 pcs slot Media Converter with one 300Watt PSU
- > Hot swappable to plug-in/plug-out media converter without any shutdown
- > Each unit can work plug on independently in the rack
- > Can be mutual cooperation, to provide their own network diagnosis
- > Provide 5VDC power supply to media converter
- > Completely conform to the requirements of the telecom operation level, average trouble-free working time is more than 50000 hours
- > Perfect after-sales service, offer three years warranty and lifelong maintenance service

#### Overview

The 2U Rack of Management Video optic transceiver & receiver is the most economical and standard 2U rack, which can satisfy the centralized use. Hot-Swap power supply continuous worked (Redundancy), and the system has protector device for excessive temperature, overvoltage and over-current. Adopt the voltage compensation technology inside, so the optic transceiver can get the reliable and accurate power supply.

#### Specifications

Capacity	14 or 16 media converters
Case construction	Aluminum/steel
Power	2 power supplies (Redundant)
LEDs	fan status slot power status power supply status
Operating Temperature	-40 to +85 C
Storage Temperature	-45 to +95 C
Relative humidity	0 to 95% (Non-condensing)
Power Voltage	AC85-260v/50Hz
MTBF	≥100000 hours

#### Product Application

