

# SG-WR15

# 15U Outdoor Wall Rack



#### Accossorios



Heavy Duty Cooling Fan (Optional : 2x4" or 4x4") Support Air Filter to prevent dust in fan set



AC Power Outlet (Optional : 4 or 6 Outlet)



Hanging Support



u-bolt (Made from Electro Gavanize steel)

## Installation Type

On Base





Wall Mount

Concrete Base

# Description

 $19^{\prime\prime}$  Wall-Rack outdoor 15U (D: 40, 50, 60cm) fiber optic made of EG steel high quality and long time for use. They can compliant with IP55, IP 65 or IP66 standard (Optional). they can accommodate the ODF fiber panel 1U or 3U. Cable entry 5 port and use 2 port cable glands EG/PG29 depand on cable diameter. The cabinet can support fiber distribution fiber optic, CCTV, IP Camera, Optical Amplifers, broadband equipment.

### Features

- 19 inch support for rack style, 15U High
- Paint&Color: made from Epoxy Polyester powder oated, Anticorrosive phosphate coating
- One door lockable and safe sealing and protection of equipment against water, water, humidity and dust, made from "Foam Gaskets" style, not rubber style
- Front door made from "CNC" Foam Gaskets" style high quality grade for waterproof and dust
- Latch made from Stainless Steel built for outdoor propose
- Provided 4mm thickness foam for protection water and rustproof for body closure
- All screw or nut made from stainless steel
- Size: 810 mm x 600 mm x (400, 500,600) mm (HighxWidthxDepth)
- Can support rack mount 1U or 3U patch panel fiber optic max capacity: 15U
- Can support cable entry 5 port and 2 cable grands EG/PG29
- Can support cable management inside easy for use cable tie lock
- $\bullet$  Can support FAN  $4x4^{\prime\prime}$  for air flow, 2 point (Top and Bottom of the Rack)
- Mounting Pole can be added at back side to support heavy weight
- Complete set tools for hang on pole and support 4 hole for wall type
- Material made from Electro Galvanized Steel 1.5mm Thickness
- Front door can open over 130 degree