

SG-XGF28

L3 28-port Managed Gigabit Fiber Switch



Rich L3 Features	L3 DHCP Server/Relay	L3 DHCP Snooping	NMS Docking
L3 OSPF Routes Support	IPv4/v6 L3 Static Route	10G SFP+ Uplink	ACL, ERPS

Functions

- Rich Layer 3 Features
- Fully L2 features provide easier manageability, security and QoS
- ITU-T G.8032 Ethernet Ring Protection Switching (ERPS)
- SNMP, WEB, CLI, SSH2.0, Telnet
- VLAN Division Voice
- IPv4/IPv6 L3 static route
- OSPF Routes dynamic routing
- SFP+ 10Gbps Fiber Long Distance
- Voice Vlan Support
- Clear Statues display including traffic, CPU, fiber consumption, per-port status
- Web-UI for easy management; CLI and Command Script for advance setting; SNMP used for popular network tools management

Overview

The SG-XGF28 series offers high performance hardware IP routing, Static route, OSPF and RIP provide dynamic routing by exchanging routing information with other Layer 3 switches and routers. With the SG-XGF28 series, customers could easily achieve a Policy-based Route (PBR), which is important when they need a Fiber Switch to switch application and short network heal time.

What is Layer 3 Switch ?

A Layer 3 switch is a specialized hardware device used in network routing. Layer 3 switches technically have a lot in common with typical routers, and not only in physical appearance. Both can support the same routing protocols, inspect incoming packets, and make dynamic routing decisions based on the source and destination addresses inside. One of the main advantages of a Layer 3 switch over a router is in the way routing decisions are performed. Layer 3 switches are much lower network latency since packets don't have to take additional steps through a router.

Major Specification

- 24 x SFP slot
- 4 x 10G SFP+ slot
- 8 x Gigabit Ethernet RJ45 (combo)
- Rich Layer 3 Features
- L3 DHCP Server/Relay
- L3 DHCP Snooping
- IPv4/IPv6 L3 static route
- OSPF Routes dynamic routing
- Surge Protection : 6KV, ESD Protection : 8KV
- Authentication: 802.1x, AAA
- DHCP Snooping prevents unauthorized router installed
- Cloud management (iOS&android mobile apps)
- L3 DHCP Snooping
- ACLs (IP standard/ MAC extended/ IP extended)

Application

· Layer3 Switch is widely used in data centers and universities, factory, enterprise, where there is a very big setup of computer networking. Owing to its features like static, dynamic routing and its fast-switching speed than a router, it is used in LAN connectivity for interconnection of several VLAN and LAN networks.

· SG-XGF28 have the skills to offload the overloaded routers. This can be done by configuring a layer-3 switch, each with a main router in a wide area networking scenario so that the switch can manage all the local level VLAN routing.

· The layer-3 switch in combination with a number of layer-2 switches supports more users to connect on the network without the need for implementation of an extra layer-3 switch and more bandwidth. Thus, it is widely implemented in universities and small-scale industries. In case if the number of end users on a network platform increases, then without any enhancement of the network, it can be accommodated in the same running scenario easily.

· A layer-3 switch is smart enough to handle and manage the routing and traffic controlling of locally connected servers and end devices utilizing its high bandwidth.



Model	Shogun SG-XGF28
<p>Hardware</p> <ul style="list-style-type: none"> • Device Interface: 24 x SFP slot 4 x 10G SFP+ slot 8 x GE RJ45 (combo) 1 x RJ45 Console Port <p>Standard</p> <p>IEEE 802.3 : Ethernet MAC Protocol IEEE 802.3i : 10BASE-T Ethernet IEEE 802.3u : 100BASE-TX Fast Ethernet IEEE 802.3ab : 1000BASE-T Gigabit Ethernet IEEE 802.3z : 1000BASE-X Gigabit Ethernet (optical fiber) IEEE 802.3ae : 10G Ethernet (optical fiber) IEEE 802.3az : Energy Efficient Ethernet IEEE 802.3ad : Standard method for performing link aggregation IEEE 802.3x : Flow control IEEE 802.1ab : LLDP/LLDP-MED (Link Layer Discovery Protocol) IEEE 802.1p : LAN Layer QoS/CoS Protocol Traffic Prioritization(Multicast filtering function) IEEE 802.1q : VLAN Bridge Operation IEEE 802.1x : Client/Server Access Control and Authentication Protocol IEEE 802.1d : STP IEEE 802.1s : MSTP IEEE 802.1w : RSTP <ul style="list-style-type: none"> • LED Indicators: PWR(Power indicator),SYS(System lights),Link(Link light), Act(data light) • Lighting Surge Protection: Surge 6KV · ESD 8KV • Mechanical Solid metal 19" 1U rack-mountable, IP30 <p>Power</p> <ul style="list-style-type: none"> • Power Input: AC 100~240V 50~60Hz <p>Switch Architecture Performance</p> <ul style="list-style-type: none"> • Switching Performance Bandwidth:128Gbps Packet Buffer Memory:95.24Mpps DDR SDRAM:512MB Flash Memory:16MB Package cache:12Mbit MAC Address:16K Jumbo frame:12Kbytes VLANs:4096 MTBF:100000 hour </p>	<p>Fiber Medium:</p> <p>Multi-mode Fiber: 850nm, 1310nm Transmission Distance: 550m/2Km Single-mode Fiber: 1310nm, 1550nm Transmission Distance: 20/40/60/80/100/120Km</p> <p>ERPS Ethernet Ring Protection</p> <ul style="list-style-type: none"> • Support G.8032 (ERPS), support 255 loops at most, and supports 1024 devices per ring. • Support STP/RSTP/MSTP(ERPS), support loop detection and self-healing, support remote loopback monitoring and control (802.3ah OAM) • Support Loop Prevention & Loop Notification <p>Software Function</p> <ul style="list-style-type: none"> • Basic function: Support hardware watchdog, factory reset, system and port LED Support global information, statistical information, log information Support User management, alarm management, configuration management Support Port rate, duplex, flow control, maximum frame length configuration Support Port mirroring, port speed limit, port energy saving • Layer 3 Interface: Support Layer 3 interface Support IPv4, IPv6 address configuration Support ARP configuration Support ND configuration • Layer 3 Routing: Support IPv4 static routing Support IPv6 static routing Support RIP V1/V2 Support OSPF • DHCP: Support DHCP server Support DHCP relay Support DHCP Snooping • VLAN: Support 4K VLAN Support 802.1Q VLAN · based on port VLAN Support Access · Trunk · Hybrid VLAN mode Support GVRP (VLAN registration protocol) Support MAC VLAN · IP VLAN Support Voice VLAN • MAC Address: Support MAC address automatic learning and aging Support Static, dynamic, filtered address table

Model	Shogun SG-XGF28
<ul style="list-style-type: none"> • Security features: <ul style="list-style-type: none"> Password protection Support Restrict user access based on port number, IP address, MAC address Support HTTPS 、SSH V1/V2 Support VLAN-IP-MAC-PORT binding Support ARP detection, IP source protection, DoS protection Support DHCP Snooping 、DHCP Attack protection Support 802.1X Certification Support AAA (Authentication, Authorization, Accounting), Support RADIUS protocol Support Port security, port isolation • Access control: <ul style="list-style-type: none"> Support L2(Layer 2)~L4(Layer 4) Packet filtering function Support Port mirroring, flow rate limiting, QoS remarking • QoS: <ul style="list-style-type: none"> Support 8 port queues Support Port priority, 802.1P priority, DSCP priority Support SP, WRR Priority scheduling algorithm • Spanning tree: <ul style="list-style-type: none"> Support STP(IEEE 802.1d), RSTP(IEEE 802.1w) and MSTP(IEEE 802.1s) protocol Support Multi-instance, Support Aggregate interface Support BPDU protection • Multicast: <ul style="list-style-type: none"> Support IGMP v1/v2/v3 Snooping Support MLD v1/v2 Snooping Support Layer 2 multicast fast leave mechanism, querier Support Layer 2 IPv4 static multicast Support Layer 2 IPv6 static multicast Support IGMP v1/v2/v3 Layer 3 multicast • Storm Suppression: <ul style="list-style-type: none"> Support multicast suppression Support broadcast storm suppression Support unknown unicast suppression • Ring protection <ul style="list-style-type: none"> Support Ring protection • Link Aggregation <ul style="list-style-type: none"> Support Static Aggregation Support LACP Dynamic Aggregation Support based on IP, MAC, mixed load-balancing modes Maximum support 8 aggregation groups (8 ports per aggregation group) • IPv6 <ul style="list-style-type: none"> Support IPv6 Ping 、IPv6 Traceroute 、IPv6 Telnet Support IPv6 SSH Support IPv6 HTTP 、IPv6 HTTPS 	<p>Management and Maintenance</p> <ul style="list-style-type: none"> Support WEB Management (HTTP 、HTTPS) Support CLI (Telnet, SSH V1/V2, Local serial port) Support SNMP V1/V2/V3 Support RMON V2 Support LLDP Device discovery Support SNTP Time synchronization Support CPU Monitoring, Memory Monitoring Support System log, classification warning Support Ping, Traceroute detection, cable detection <p>Environment</p> <ul style="list-style-type: none"> • Operating Temperature: -10°C to +50°C • Storage Temperature: -40°C to +85°C • Working Humidity: 10%~90%, non-condensing • Storage Humidity: 5%~90%, non-condensing <p>Standard package of switch</p> <ul style="list-style-type: none"> • Product size: 44x20.5x4.4 cm • Package Dimensions: 50x29x8.5 cm • Package Weight: N.W: 3.06KG / G.W: 3.63KG • Package content: Switch x 1, QIG x 1, Power cord x 1, Serial cable x 1, Rack ear x 1 <p>Standard carton package</p> <ul style="list-style-type: none"> Carton Dimensions: 52x44.5x31 cm Packing QTY: 5 PCS Packing weight: 19.15KGS <p>Ordering Information</p> <ul style="list-style-type: none"> • Model: SG-XGF28 Name: L3 28-port Managed Gigabit Fiber Switch with 10G.