

## SG-OR15

15U 19" Outdoor Rack



### Accessories



Heavy duty cooling fan (optional : 2x4" or 4x4") support air filter to prevent dust in fan set




AC Power Outlet (optional : 4 or 6 Outlet)



Hanging support



U-bolt for electric pole (Made from Electro Gavanize steel)



12 or 24Core Splice Tray (Single mode&Multimode) support to install by hanging in Rack

### Description

19" Outdoor Rack 15U fiber optic made of EG steel high quality and long time for use. They can compliant with IP55, IP 65 or IP66 standard (Optional). they can accommodate the ODF fiber panel 1U or 3U. Cable entry 5 port and use 2 port cable glands EG/PG29 depend on cable diameter. The cabinet can support fiber distribution fiber optic, CCTV, IP Camera, Optical Amplifiers, broadband equipment.

### Features

- 19 inch support for rack style, 15U High
- Paint&Color : made from Epoxy Polyester powder coated (color outdoor type), Anti- corrosive phosphate coating
- One door lockable and safe sealing and protection of equipment against water, water, humidity and dust, made from " Foam Gaskets" style, not rubber style
- Front door made from "CNC" Foam Gaskets" style high quality grade and front edge-roll for waterproof and humidity protection
- Latch made from Stainless Steel built for outdoor propose
- Provided 4mm thickness foam for protection water and rustproof for body closure
- All screw & nut and master key made by stainless steel
- Size: 810 mm x 600 mm x 500 mm (HighxWidthxDepth)
- Can support rack mount 1U or 3U patch panel fiber optic max capacity: 15U
- Can support cable entry 5 port and 2 cable grands EG/PG29
- Can support cable management inside easy for use cable tie lock
- Can support 4pcs (max) FAN 4x4" for air flow, 2 point (2pcs on Top and 2pc on Bottom of the Rack)
- Two mounting pole at front for 19" device stick (can be added 2 mounting pole at back side to support heavy weight
- Complete set tools for hang on pole and support 4 hole for wall type
- Material made from Electro Galvanized Steel 1.5mm Thickness
- Front door can open over 130 degree opening service
- 12 or 24 core Splice Tray (Singlemode&Multimode) support to install by hanging in Rack
- Support concrete base by screw&nut on 2 side of cabinet's base leg.

### Installation Type



Concrete Base

