

SG-625

IP68 Outdoor Camera Housing (With IR)



Features

- IP68, NEMA-6P enclosure rating
- IK10 Impact Protection Rating (IEC 62262)
- Designed for indoor and outdoor applications
- PoE 48VDC Input/Output Power
- Built-in heater and blower
- Adjustable sliding camera tray (Removable Camera Sled)
- Cable entry glands and mounting holes on bottom of housing
- Die-cast aluminum construction with high impact resistance
- Side opening for easy installation locked by stainless screw
- Bundled internal cable managed bracket
- Built-in 50M Infrared module with double glass
- Can supply power from PoE Injector or PoE Switch for Infrared, Fan and Heater for control inside temperature (also support for IP camera by PoE and Non-PoE)
- Camera housing & mounting made a complete set with Die-cast Aluminum (ivory color)

Technical Specification

Physical

Material	Die-cast Aluminum
Surface&Color	White Polyester Power Coat Finish
Viewing Window	Tempered glass
Latch	Dual side (locking by screw)
Camera Mounting	Removable camera metal sled
Blower/Heater Control	On at 35 °C,Off at 25 °C (Blower) On at 15 °C,Off at 25 °C (Heater)
Input Power	30W PoE (IEEE802.3af & IEEE802.3at)
Network Interface	RJ-45 x 2 (PoE Input/PoE Output)
Internal Usable Space	100 mm x 80 mm x 250 mm (W x H x L)
Dimensions	145 mm x 109 mm x 406 mm (W x H x L)
Window Material	2 mm. Tempered Glass
Viewing Area	92 mm x 76 mm (W x H)
Operating Temperature	-50 °C to 50 °C
Relative Humidity	5 % to 95 % noncondensing
Weight	3.6 kg
Standard Approvals	FCC, CE (EN 60529), RoHS