

60W Speaker

Compact high performance Speaker



Features

- Various mount brackets
- Stylish and highly rigid speaker casing design
- For any environment (waterproof design. The speakers may also be re-painted as desired)
- Built-in speaker protection
- Impedance matching (for optimal amplifier/speaker performance)
- Easy connecting (Push-in terminals allow quick connections)

Descriptions

The speaker casing comes with a design that is highly stylish, so it blends well into a room's decor and can be attractively installed. The graceful, lightly convex bulge on the side of the casing is also part of a rigidity-enhancing casing construction that works for clear sound reproduction.

Specifications

Enclosure Type	Bass-reflex type
Power Handling Capacit	—
Rated Input	60W
Rated Impedance	8 Ω
	100V line: 170Ω (60W), 330 Ω (30W), 670 Ω (15W), 3.3 kΩ (3W)
	70V line: 83Ω (60W), 170Ω (30W), 330 Ω (15W), 670 Ω (7.5W), 3.3 kΩ (1.5W)
Sensitivity	92 dB (1W, 1m) at installation in 1/2 free sound field
	93 dB (1W, 1m) at installation in 1/2 free sound field (with horn adapter)
Frequency Response	65 - 20,000 Hz, -10 dB at installation in 1/2 free sound field
Crossover Frequency	2.5 kHz
Directivity Angle	Horizontal: 110°, Vertical: 100° Horizontal: 80°, Vertical: 80° (with horn adapter)
Speaker Component	Low frequency: 20 cm (8") cone-type High frequency: 25 mm (1") dome tweeter
Input Terminal	Push-in terminal
Water Protection	—
Operating Temperature	—
Finish	Enclosure: HIPS, white
Dimensions	244 (W) × 373 (H) × 235 (D) mm (9.61" × 14.69" × 9.25")
Weight	7.4 kg (16.31lb) (including the supplied brackets)
Accessories	Speaker bracket × 1, Joint bracket × 1, Wall bracket × 1, Bracket fixing screw × 1 set, Horn adapter x 1, Horn adapter mounting screw x 4